

Thread Size d		M5	M6	M8	M10	(M10) ①	M12	M14	M16	M20	M24	M30	M36
P	Picth	0.80	1.00	1.25	1.50	1.50	1.75	2.00	2.00	2.50	3.00	3.50	4.00
s	max	8.00	10.00	13.00	16.00	15.00	18.00	21.00	24.00	30.00	36.00	46.00	55.00
	min	7.78	9.78	12.73	15.73	14.73	17.73	20.67	23.67	29.16	35.00	45.00	53.80
e	max	9.24	11.55	15.01	18.48	17.32	20.78	24.25	27.71	34.64	41.57	53.12	63.51
	min	8.79	11.05	14.38	17.77	16.64	20.03	23.35	26.75	32.95	39.55	50.85	60.79
m	max	2.70	3.20	4.00	5.00	5.00	6.00	7.00	8.00	10.00	12.00	15.00	18.00
	min	2.45	2.90	3.70	4.70	4.70	5.70	6.42	7.42	9.10	10.90	13.90	16.90
c	max	/	/	/	/	/	/	/	/	0.80	0.80	0.80	0.80
	min	/	/	/	/	/	/	/	/	0.40	0.40	0.40	0.40
d_w	min	6.90	8.90	11.60	14.60	8.00	16.60	19.60	22.50	27.70	33.20	42.80	51.10

①,When M10 nuts are ordered, nuts with 16 mm width across flats shall be furnished, unless 15 mm width across flats is specified.