

Nominal Diameter d			Φ1.5	Φ2	Φ2.5	Φ3	Φ3.5	Φ4	Φ5	Φ6	Φ8	Φ10	Φ12	Φ14	Φ16	Φ20
d	before mounting	max	1.71	2.21	2.73	3.25	3.79	4.30	5.35	6.40	8.55	10.65	12.75	14.85	16.90	21.00
		min	1.61	2.11	2.62	3.12	3.64	4.15	5.15	6.18	8.25	10.30	12.35	14.40	16.40	20.40
d ₂	before mounting	max	1.40	1.90	2.40	2.90	3.40	3.90	4.85	5.85	7.80	9.75	11.70	13.60	15.60	19.60
a	=		0.50	0.70	0.70	0.90	1.00	1.10	1.30	1.50	2.00	2.50	3.00	3.50	4.00	4.50
s			0.17	0.22	0.28	0.33	0.39	0.45	0.56	0.67	0.90	1.10	1.30	1.60	1.80	2.20
Minimum Double Shear,kN	Steel		1.90	3.50	5.50	7.60	10.00	13.50	20.00	30.00	53.00	84.00	120.00	165.00	210.00	340.00
	Stainless steel		1.45	2.50	3.80	5.70	7.60	10.00	15.50	23.00	41.00	64.00	91.00	/	/	/