

Thread Size d		M2	M2.5	M3	(M3.5)	M4	M5	M6	M8	M10	
<b>P</b>	Pitch	0.4	0.45	0.5	0.6	0.7	0.8	1	1.25	1.5	
<b>b</b>	min	25	25	25	38	38	38	38	38	38	
<b>d<sub>k</sub></b>	theoretical	max	4.4	5.5	6.3	8.2	9.4	10.4	12.6	17.3	20
		min	3.8	4.7	5.5	7.30	8.40	9.30	11.30	15.80	18.30
	actual	max	3.5	4.4	5.2	6.9	8	8.9	10.9	15.4	17.8
<b>k</b>	max	1.2	1.5	1.65	2.35	2.7	2.7	3.3	4.65	5	
<b>x</b>	max	1	1.1	1.25	1.5	1.75	2	2.5	3.2	3.8	
<b>r</b>	max	0.5	0.6	0.8	0.9	1	1.3	1.5	2	2.5	
<b>Socket No.</b>		0	1	1	2	2	2	3	4	4	
<b>M<sub>1</sub></b>	Series 1 /Type H	1.9	2.9	3.2	4.4	4.6	5.2	6.8	8.9	10	
<b>Penetration depth</b>	Series 1 /Type H	min	0.9	1.4	1.7	1.9	2.1	2.7	3	4	5.1
		max	1.2	1.8	2.1	2.4	2.6	3.2	3.5	4.6	5.7
<b>M<sub>2</sub></b>	Series 1 /Type Z	1.9	2.8	3	4.1	4.4	4.9	6.6	8.8	9.8	
<b>Penetration depth</b>	Series 1/Type Z	min	0.95	1.48	1.76	1.75	2.06	2.6	3	4.15	5.19
		max	1.2	1.73	2.01	2.2	2.51	3.05	3.45	4.6	5.64
<b>M<sub>1</sub></b>	Series 2 /Type H	1.9	2.7	2.9	4.1	4.6	4.8	6.6	8.7	9.6	
<b>Penetration depth</b>	Series 2 /Type H	min	0.9	1.25	1.4	1.6	2.1	2.3	2.8	3.9	4.8
		max	1.2	1.55	1.8	2.1	2.6	2.8	3.3	4.4	5.3
<b>M<sub>2</sub></b>	Series 2/Type Z	1.9	2.5	2.8	4	4.4	4.6	6.3	8.5	9.4	
<b>Penetration depth</b>	Series 2/Type Z	min	0.95	1.22	1.48	1.61	2.06	2.27	2.73	3.87	4.78
		max	1.2	1.47	1.73	2.05	2.51	2.72	3.18	4.32	5.23

①, Series 1 : a<sub>max</sub> = 2.5P ; Series 2 : a<sub>max</sub> = 2P

②, Material:

a) Steel, Strength class: 8.8; Standard ISO 898-1

b) Stainless steel, Strength class: A2-70; Standard ISO 3506-1

c) Non-ferrous metal, Strength class: CU2, CU3 (at the choice of the manufacturer ); Standard ISO 8839