

Thread Size		2#	3#	4#	5#	6#	8#	10#	12#	1/4	5/16	3/8	7/16	1/2
d	Nominal Size	0.086	0.099	0.112	0.125	0.138	0.164	0.19	0.216	0.25	0.3125	0.375	0.4375	0.5
PP		56	48	40	40	32	32	24	24	20	18	16	14	13
M	Ref.	0.081	0.094	0.111	0.111	0.132	0.155	0.178	0.2	0.221	0.266	0.312	0.352	0.446
Socket No.		T7	T8	T9	T10	T15	T20	T25	T27	T30	T40	T45	T50	T55
P	max	0.035	0.035	0.04	0.045	0.06	0.065	0.075	0.08	0.09	0.12	0.13	0.15	0.17
	min	0.03	0.03	0.035	0.035	0.05	0.05	0.06	0.065	0.075	0.105	0.115	0.135	0.155
d_k	Ref.	0.136	0.156	0.177	0.198	0.218	0.259	0.3	0.341	0.396	0.494	0.593	0.691	0.79
d_c	max	0.202	0.232	0.261	0.291	0.321	0.38	0.439	0.498	0.576	0.719	0.861	1.004	1.146
	min	0.186	0.215	0.243	0.272	0.301	0.358	0.416	0.473	0.548	0.687	0.825	0.963	1.101
k	max	0.062	0.07	0.079	0.088	0.096	0.113	0.13	0.148	0.17	0.211	0.253	0.294	0.335
	min	0.05	0.058	0.067	0.075	0.084	0.101	0.118	0.134	0.157	0.197	0.238	0.278	0.319
c	Ref.	0.03	0.03	0.03	0.04	0.04	0.04	0.05	0.05	0.05	0.06	0.06	0.07	0.09

①,Where specifying nominal size in decimals, zeros preceding the decimal and in the fourth decimal place shall be omitted.