

Thread Size		M2	M2.5	M3	(M3.5)	M4	M5	M6	M8	M10
P	Pitch	0.4	0.45	0.5	0.6	0.7	0.8	1	1.25	1.5
a	max	0.8	0.9	1	1.2	1.4	1.6	2	2.5	3
d_k	max=nominal size	4	5	5.6	7	8	9.5	12	16	20
	min	3.7	4.7	5.3	6.64	7.64	9.14	11.57	15.57	19.48
d_s	max	2.6	3.1	3.6	4.1	4.7	5.7	6.8	9.2	11.2
k	max=nominal size	1.6	2.1	2.4	2.6	3.1	3.7	4.6	6	7.5
	min	1.46	1.96	2.26	2.46	2.92	3.52	4.3	5.7	7.14
r	min	0.1	0.1	0.1	0.1	0.2	0.2	0.25	0.4	0.4
R	=	3.2	4	5	6	6.5	8	10	13	16
x	max	1	1.1	1.25	1.5	1.75	2	2.5	3.2	3.8
Socket No.		T6	T8	T10	T15	T20	T25	T30	T45	T50
A	Ref.	1.75	2.4	2.8	3.35	3.95	4.5	5.6	7.95	8.95
t	max	0.77	1.04	1.27	1.33	1.66	1.91	2.42	3.18	4.02
	min	0.63	0.91	1.01	1.07	1.27	1.52	2.02	2.79	3.62