

For thread diameter		M2	M2.5	M3	M3.5	M4	M5	M6	M7	M8	M10
d	min=nominal size (H14)	2.20	2.70	3.20	3.70	4.30	5.30	6.40	7.40	8.40	10.50
	max	2.45	2.95	3.50	4.00	4.60	5.60	6.76	7.76	8.76	10.93
d _c	max=nominal size (h14)	5.00	6.00	7.00	8.00	9.00	11.00	14.00	17.00	18.00	23.00
	min	4.70	5.70	6.64	7.64	8.64	10.57	13.57	16.57	17.57	22.48
h		0.40	0.50	0.60	0.80	1.00	1.20	1.50	1.75	2.00	2.50
H	max	0.60	0.72	0.85	1.06	1.30	1.55	2.00	2.30	2.60	3.20
	min	0.50	0.61	0.72	0.92	1.12	1.35	1.70	2.00	2.24	2.80
per 1000 units ≈ kg		0.05	0.09	0.14	0.25	0.38	0.69	1.43	2.53	3.13	6.45

For thread diameter		M12	M14	M16	M18	M20	M22	M24	M27	M30
d	min=nominal size (H14)	13.00	15.00	17.00	19.00	21.00	23.00	25.00	28.00	31.00
	max	13.43	15.43	17.43	19.52	21.52	23.52	25.52	28.52	31.62
d _c	max=nominal size (h14)	29.00	35.00	39.00	42.00	45.00	49.00	56.00	60.00	70.00
	min	28.48	34.38	38.38	41.38	44.38	48.38	55.26	59.26	69.26
h		3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00
H	max	3.95	4.65	5.25	5.80	6.40	7.05	7.75	8.35	9.20
	min	3.43	4.04	4.58	5.08	5.60	6.15	6.77	7.30	8.00
per 1000 units ≈ kg		12.40	21.60	30.40	38.90	48.80	63.50	92.90	113.00	170.00