

For thread diameter ④		M2.5 ① ②	M3 ①	M3.5 ①	M4	M5	M6	M8	M10
d ③	min=nominal size	2.25	2.70	3.20	3.60	4.55	5.40	7.30	9.20
	max	2.35	2.80	3.32	3.72	4.67	5.52	7.45	9.35
d _c	max=nominal size	7.00	8.00	8.00	9.00	11.00	12.00	15.00	21.00
	min	6.78	7.78	7.78	8.78	10.73	11.73	14.73	20.67
h	Nominal Size	0.50	0.50	0.50	0.80	0.80	0.80	1.00	1.00
	max	0.55	0.55	0.55	0.86	0.86	0.86	1.07	1.07
	min	0.45	0.45	0.45	0.74	0.74	0.74	0.93	0.93
H	max	1.05	1.05	1.15	1.65	1.75	2.00	2.40	2.60
	min	0.90	0.90	1.00	1.50	1.60	1.85	2.20	2.40
per 1000 units ≈ kg		0.13	0.17	0.16	0.34	0.49	0.57	1.06	2.20

①,For this size, no specifications have been made for the residual spring force in DIN 267 part 26.

②,For this size, no specifications have been made for permanent set in DIN 267 part 26

③,The tolerances specified apply to the washer in the flat-pressed condition.

④,As specified in DIN 267-26

⑤,Technical delivery conditions:

Washers shall be made of spring steel (FSt) and comply with the technical delivery conditions specified in DIN 267-26