

For thread diameter ②		M2.5	M3	M3.5	M4	M5	M6	(M7) ③	M8	M10	M12 ①
d	min=nominal size	2.25	2.70	3.20	3.60	4.55	5.50	6.50	7.40	9.30	11.00
	max	2.35	2.80	3.30	3.75	4.75	5.70	6.70	7.65	9.55	11.30
b	Nominal Size	1.00	1.30	1.30	1.50	1.80	2.50	2.50	3.00	3.50	4.00
	max	1.10	1.40	1.40	1.60	1.90	2.65	2.65	3.15	3.70	4.20
	min	0.90	1.20	1.20	1.40	1.70	2.35	2.35	2.85	3.30	3.80
s	Nominal Size	0.60	0.70	0.70	0.80	1.00	1.30	1.30	1.60	1.80	2.10
	max	0.70	0.80	0.80	0.90	1.10	1.40	1.40	1.70	1.90	2.25
	min	0.50	0.60	0.60	0.70	0.90	1.20	1.20	1.50	1.70	1.95
h	max	1.10	1.30	1.30	1.40	1.70	2.20	2.20	2.75	3.15	3.65
	min	0.90	1.10	1.10	1.20	1.50	2.00	2.00	2.45	2.85	3.35
d <sub>c</sub>	max	4.55	5.60	6.10	6.95	8.55	11.00	12.00	13.95	16.95	19.70
per 1000 units ≈ kg		0.06	0.09	0.10	0.15	0.30	0.64	0.72	1.23	2.00	3.10

①,For this size, no specifications have been made for the residual spring force in DIN 267 Part 26.

②,As specified in DIN 267 Part 26.

③,For replacement and maintenance purposes

④,Technical delivery conditions:

Washers shall be made of spring steel (FSt) and comply with the technical delivery conditions specified in DIN 267-26