




Thread Size d			M5	M6	M8	M10	M12	(M14)	M16
P	Pitch		0.8	1	1.25	1.5	1.75	2	2
b	ref.	L≤125	16	18	22	26	30	34	38
		125<L≤200	/	/	28	32	36	40	44
		L>200	/	/	/	/	/	/	57
c	min		1	1.1	1.2	1.5	1.8	2.1	2.4
d _a	Form F	max	5.7	6.8	9.2	11.2	13.7	15.7	17.7
	Form U	max	6.2	7.5	10	12.5	15.2	17.7	20.5
d _c	max		11.4	13.6	17	20.8	24.7	28.6	32.8
d _s	max		5	6	8	10	12	14	16
	min		4.82	5.82	7.78	9.78	11.73	13.73	15.73
d _u	max		5.5	6.6	8.8	10.8	12.8	14.8	17.2
d _w	min		9.4	11.6	14.9	18.7	22.5	26.4	30.6
e	min		7.59	8.71	10.95	14.26	16.5	19.86	23.15
k	max		5.6	6.9	8.5	9.7	12.1	12.9	15.2
k ₁	min		2.3	2.9	3.8	4.3	5.4	5.6	6.8
f	max		1.4	1.6	2.1	2.1	2.1	2.1	3.2
r ₁	min		0.2	0.25	0.4	0.4	0.6	0.6	0.6
r ₂	max		0.3	0.4	0.5	0.6	0.7	0.9	1
r ₃	max		0.25	0.26	0.36	0.45	0.54	0.63	0.72
	min		0.10	0.11	0.16	0.20	0.24	0.28	0.32
r ₄	Ref.		4	4.4	5.7	5.7	5.7	5.7	8.8
s	max		7	8	10	13	15	18	21
	min		6.78	7.78	9.78	12.73	14.73	17.73	20.67
V	max		0.15	0.20	0.25	0.30	0.35	0.45	0.50
	min		0.05	0.05	0.10	0.15	0.15	0.20	0.25
L ₀			25	30	35	40	45	50	55

①, Reduce shank type only when L > L₀