




Thread Size d		10#	1/4	5/16	3/8	7/16	1/2	5/8	3/4
d		0.1900	0.2500	0.3125	0.3750	0.4375	0.5000	0.6250	0.7500
PP	UNC	24	20	18	16	14	13	11	10
d_s	max	0.199	0.260	0.324	0.388	0.452	0.515	0.642	0.768
	min	0.182	0.237	0.298	0.360	0.421	0.483	0.605	0.729
d_k	max	0.548	0.682	0.821	0.960	1.093	1.233	1.495	1.754
	min	0.500	0.625	0.750	0.875	1.000	1.125	1.375	1.625
c	min	0.015	0.018	0.023	0.027	0.030	0.035	0.038	0.041
k	max	0.131	0.154	0.184	0.212	0.235	0.265	0.316	0.368
	min	0.112	0.135	0.159	0.183	0.205	0.229	0.272	0.314
s	max	0.199	0.260	0.324	0.388	0.452	0.515	0.642	0.768
	min	0.185	0.245	0.307	0.368	0.431	0.492	0.616	0.741
e	min	0.236	0.321	0.408	0.481	0.571	0.657	0.807	0.983
k_1	max	0.125	0.156	0.219	0.250	0.281	0.312	0.406	0.500
	min	0.094	0.125	0.188	0.219	0.250	0.281	0.375	0.469
h	min	0.181	0.222	0.296	0.345	0.385	0.428	0.552	0.662
r	max	0.031	0.031	0.031	0.047	0.047	0.047	0.078	0.078

①, Minimum Thread Length: The minimum length of thread shall be equal to twice the basic bolt diameter plus 0.25 in. for nominal bolt lengths of 6 in. or shorter, and twice the basic bolt diameter plus 0.50 in. for longer nominal lengths. Bolts of nominal lengths too short to accommodate the minimum thread lengths shall be threaded full length. The length from the head or neck to the first complete (full form) thread shall not exceed the length of 2-1/2 threads for sizes up to and including 1 in., and 3-1/2 threads for sizes over 1 in.