




$$\alpha = 0.75^\circ \pm 0.75^\circ$$

$$\delta = 15^\circ \sim 25^\circ$$

$$\theta = 90^\circ \sim 120^\circ$$

Screw Thread d			M8	M10	M12	(M14)	M16	M20
P	Pitch	Fine thread -1	1	1	1.5	1.5	1.5	1.5
		Fine thread -2	-	1.25	1.25	-	-	-
c	min		1.2	1.5	1.8	2.1	2.4	3
d _a	min		8	10	12	14	16	20
	max		8.75	10.8	13	15.1	17.3	21.6
d _c	max		17.9	21.8	26	29.9	34.5	42.8
d _w	min		15.8	19.6	23.8	27.6	31.9	39.9
e	min		14.38	17.77	20.03	23.36	26.75	32.95
h	max		11.1	13.5	16.1	18.2	20.3	24.8
	min		10.4	12.8	15.4	16.9	19	22.7
m	min		7.6	9.6	11.6	13.3	15.3	18.7
m _w	min		4.6	5.9	6.8	7.7	8.9	10.7
s	max		13	16	18	21	24	30
	min		12.73	15.73	17.73	20.67	23.67	29.16
r	max		0.48	0.6	0.72	0.88	0.96	1.2

①, Material:

Steel, Property class 8: Type 1. Property class 8: $d \leq M16$, Type 2; $d > M16$, Type 1. Property class 10: Type 2. Standard prEN ISO 2320